

# 9226-7

## 92x92x25mm (3.62x3.62x0.98 in) - 7 blade



- Bearing System----- 2 Ball Bearing
- Life Expectancy----- Ball 70000hrs @ 3600RPM @ 30° C
- Frame----- Thermoplastic PBT+30% GF, UL94-V0
- Impeller----- Thermoplastic PBT+15% GF, UL94-V0
- Lead Wire ----- UL 1007, AWG 24, 260 ± 10mm, Red(+), Black(-)
- Protection ----- Locked rotor protection
- IP Grade ----- IP51, IP54, IP56, IP67



IATF16949:2016  
ISO 9001:2015  
ISO 14001:2015



Dim: 558x373x349 mm  
N.W.: 15.5 kgs  
G.W.: 18.7 kgs  
Q' TY: 135 pcs

FUNCTIONS	PART NUMBER	RATED (VDC)	LABEL CURRENT	ACTUAL CURRENT	POWER (WATTS)	SPEED (RPM)	AIRFLOW (CFM)(m³/min)		PRESSURE (mmAq)(In H <sub>2</sub> O)		NOISE (dBA)	WEIGHT (Q'TY/CTN)
1b:AS 2a:FG 2b:RD 2c:RDb	C9226L05BPLPxy-7	05 (04-06)	0.330	0.240	1.20	2200	48.50	1.37	2.33	0.09	27.60	114.6g (135pcs)
	C9226X12BPLPxy-7	12 (07-14)	0.600	0.440	5.28	3600	80.10	2.27	5.79	0.23	42.30	114.6g (135pcs)
	C9226H12BPLPxy-7		0.320	0.230	2.76	3000	67.70	1.92	4.32	0.17	36.90	
	C9226M12BPLPxy-7		0.230	0.170	2.04	2600	58.50	1.66	3.29	0.13	32.80	
	C9226L12BPLPxy-7	24 (15-27)	0.150	0.110	1.32	2200	48.50	1.37	2.33	0.09	27.60	114.6g (135pcs)
	C9226X24BPLPxy-7		0.320	0.250	6.00	3600	80.10	2.27	5.79	0.23	42.30	
	C9226H24BPLPxy-7		0.180	0.118	2.84	3000	67.70	1.92	4.32	0.17	36.90	
	C9226M24BPLPxy-7	24 (15-27)	0.143	0.083	2.00	2600	58.50	1.66	3.29	0.13	32.80	114.6g (135pcs)
	C9226L24BPLPxy-7		0.085	0.055	1.32	2200	48.50	1.37	2.33	0.09	27.60	
C9226L24BPLPxy-7	0.085		0.055	1.32	2200	48.50	1.37	2.33	0.09	27.60		
1b:AS 2a:FG 2b:RD 2c:RDb	R9226H05BPLPxy-7	05 (04-06)	0.870	0.700	3.50	3000	67.70	1.92	4.32	0.17	36.90	114.6g (135pcs)
	R9226M05BPLPxy-7		0.630	0.480	2.40	2600	58.50	1.66	3.29	0.13	32.80	
	R9226L05BPLPxy-7		0.330	0.240	1.20	2200	48.50	1.37	2.33	0.09	27.60	
	R9226Y12BPLPxy-7	12 (07-14)	0.860	0.600	7.20	4000	89.00	2.52	7.00	0.28	44.90	114.6g (135pcs)
	R9226X12BPLPxy-7		0.600	0.440	5.28	3600	80.10	2.27	5.79	0.23	42.30	
	R9226H12BPLPxy-7		0.320	0.230	2.76	3000	67.70	1.92	4.32	0.17	36.90	
	R9226M12BPLPxy-7	24 (15-27)	0.230	0.170	2.04	2600	58.50	1.66	3.29	0.13	32.80	114.6g (135pcs)
	R9226L12BPLPxy-7		0.150	0.110	1.32	2200	48.50	1.37	2.33	0.09	27.60	
	R9226Y24BPLPxy-7		0.480	0.300	7.20	4000	89.00	2.52	7.00	0.28	44.90	
	R9226X24BPLPxy-7	24 (15-27)	0.320	0.250	6.00	3600	80.10	2.27	5.79	0.23	42.30	114.6g (135pcs)
	R9226H24BPLPxy-7		0.180	0.118	2.83	3000	67.70	1.92	4.32	0.17	36.90	
	R9226M24BPLPxy-7		0.143	0.083	1.99	2600	58.50	1.66	3.29	0.13	32.80	
R9226L24BPLPxy-7	24 (15-27)	0.085	0.055	1.32	2200	48.50	1.37	2.33	0.09	27.60	114.6g (135pcs)	
R9226L24BPLPxy-7		0.085	0.055	1.32	2200	48.50	1.37	2.33	0.09	27.60		
R9226L24BPLPxy-7		0.085	0.055	1.32	2200	48.50	1.37	2.33	0.09	27.60		

Remark:

1. Part no. suffix: "xy" =Function detail or "x" =Function number. and "y" =customer ID

2. C series – STANDARD series:

Uses a 2 coil complementary type drive offering low cost and limited functions.

3. R series – STANDARD series:

Uses a 2 coil complementary type drive offering low cost, applicable for higher power demanding applications and have more functions

